

FIREBOND® CONCENTRATE

Bonding agent

Description

Firebond® is an Underwriters Laboratories Inc. (UL) classified bonding agent approved for use with any of the fire protection products manufactured by W. R. Grace & Co. Firebond is water based, nonflammable and ready to use. Firebond is classified for use with Grace fire protection products in accordance with ASTM E119 and E84 and listed in the UL Fire Resistance Directory, category CBUI encapsulants.

Use

Firebond may be used as a bonding agent or surface sealer for the following applications:

1. As a bonding agent over polystyrene or urethane foam insulation prior to application of Monokote® Z-3306 Thermal Barrier.
2. As a bonding agent over primed/painted structural steel (columns and beams)¹ prior to application of Monokote MK-6®/HY®, MK-6/HY ES™, MK-6s, Z-106, Z-106/HY, Z-106/G, Z-146 and Retro-Guard® RG.²
3. As a bonding agent over concrete floor and/or roof units (including slab, panjoist, hollow-core or precast plank or TEE units) prior to application of the products listed in item 2.
4. As a surface sealer (where specified) over any of the above products. Coverage rate requirements will vary based on the project requirements. Where specified, a surface sealer shall be installed in one or more coats in such a manner that the sealer does not saturate the fire protection product. The fire protection product shall be substantially dry prior to sealer application.

Application

Firebond can be applied with most major brands of airless latex paint spray equipment. Firebond may also be applied with a common garden sprayer, paint brush or roller.

• Coverage:

- Firebond at full concentrated strength—
up to 1000 ft²/gal
- Firebond diluted 1:1 (with water)—
up to 500 ft²/gal

Clean Up

Clean tools and drippings with warm soapy water before Firebond dries.

Technical Support

Refer to W. R. Grace & Co. product literature to determine acceptability of fire protection products for the intended use. Any inquiry related to products manufactured by W. R. Grace & Co. should be addressed to:

W.R. Grace & Co.
62 Whittemore Avenue
Cambridge, MA 02140
or call toll free: 866-333-3SBM (3726)—
Customer Service Center

Physical Properties

Property	Typical Value
Volatile	Water
Actual VOC content	14.3 ± 10 g/L
Average particle size	0.2 microns
Flash point	Noncombustible (water-based)
Odor	Similar to latex house paint
Shelf life at 78°F	36 months minimum, (in originally factory sealed containers)
Weight per gallon at 78°F	8.8 lbs
Dry time at 78°F	To touch: 1–2 hours Additional coats: (when dry)
Fire rating ASTM E84	Class "A"
Flame spread	5
Smoke developed	5

Firebond is manufactured by Fiberlock Technologies Inc. for W. R. Grace & Co. Any inquiry related to products manufactured by Fiberlock Technologies, Inc., should be addressed to:

Fiberlock Technologies, Inc.
150 Dascomb Road
Andover, MA 01810
or call toll free: 800-FIBERLK

Grace Construction Products provides technical support for all of its products. The Fiberlock Technologies, Inc. Material Safety Data Sheet for Firebond is available at our web site, www.graceconstruction.com.

Warranty

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable. However, since the conditions of use and application are beyond our control, Grace Construction Products shall not be liable for any damage, direct or consequential, resulting from the use of this material or design. Grace Construction Products' only warranty shall be to replace any of its products found to be defective.

Safety

KEEP OUT OF REACH OF CHILDREN.
Keep from freezing. Do not store at temperatures above 100°F.

Availability

Grace Construction Products is the exclusive supplier of Firebond Concentrate			
Description	Part No.	Volume	Std. Pk.
5 gal (19 L) pail	1378	1,155 in. ³ (18,942 cm ³)	1
55 gal (208.2 L) drum	1379	12,705 in. ³ (208,197 cm ³)	1

Footnotes

- All paints and primers require prior testing and approval by W. R. Grace & Co. for verification of compliance with the "Coating Materials" section of the Underwriters Laboratories, Inc. Fire Resistance Directory for requirements/restrictions to the use of primed/painted structural steel in fire resistance designs.
- The use of Retro-Guard RG is often associated with abatement projects. These products are not substitutes for UL classified post-removal lockdowns. Refer to the Encapsulant Materials (CBUI) category of the UL Fire Resistance Directory for additional information.



www.graceconstruction.com

For technical assistance call toll free at 866-333-3SBM (3726)

Firebond is a registered trademark of Fiberlock Technologies, Inc. Monokote, MK-6, HY and Retro-Guard are registered trademarks and ES is a trademark of W. R. Grace & Co.-Conn.

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate and is offered for the users' consideration, investigation and verification, but we do not warrant the results to be obtained. Please read all statements, recommendations or suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation or suggestion is intended for any use which would infringe any patent or copyright. W. R. Grace & Co.-Conn., 62 Whittemore Avenue, Cambridge, MA 02140. In Canada, Grace Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

This product may be covered by patents or patents pending.
MK-005A Printed in U.S.A. 12/07

Copyright 2007. W. R. Grace & Co.-Conn.
FA/LI/1M

GRACE